

AEROSOLS

Product	Description / Type	Temperature Range	Applications / Remarks
MOLYGRAF 106-M	Resin bonded Molybdenum Disulphide	- 40° C to + 375° C	Inaccessible machine parts, drills, tapes, machine tools, pivot, linkages chains, sleeves, gears, business machines, etc.
MOLYGRAF DRIKOTE	Dry Molybdenum Disulphide powder in aerosol	- 65° C to +450° C	Bearings, threaded connections, bushes, pins, sprockets, Splines, Sleeves, Hinges, Journals, shafts, Slides, Rams, Chains, Wheels, Conveyors, Plungers, Locks etc.
MOLYGRAF-106 (G)	Resin bonded graphite.	- 40° C to + 900° C	Parting agent during sintering of diamond tools. Also used as conductive coating of surfaces requiring Elector Static Discharge.
MOLYGRAF-106 (M) GLASS	Resin bonded, high temperature resistance Molybdenum Disulphide base.	- 40° C to + 900° C	Parting agent for delivery lines (chute) in glass industries.
MOLYGRAF-TEF-SPRAY	Resin bonded PTFE spray	- 100° C to + 265° C	Sliding surfaces operating in wide temperature range. Resist most acid, Chemicals, Solvents.
MOLYGRAF-CZG SPARY	Cold Zinc Galvanizing Spray	- 20° C to + 375° C	Long term rust protection for welded surfaces, bridges, fabricated steel structures, marine applications, aerospace, antenna, relay towers, off shore, on shore rigs, chemical plants and industrial maintenance
CORELA-P	Wax coating rust preventer	-	Effective rust/corrosion prevention of all kind of machined parts, tools, dies, jigs, fixtures, molds.
RUSTLUB	Solvent based rust loosener.	-	Easy re-opening of rusted mechanisms like fasteners, shafts, studs, etc.
MOLYGRAF BELT DRESSING SPRAY	Belt dressing spray	-	Tightening of loose V belts and flat belts made from rubber or synthetic materials.
MOLYGRAF-ECC	Solvent based electrical contact cleaner	-	Cleaning of electrical / electronic contacts in switches, breakers, contactors, tuners, solenoid valves, tape changers, etc.
MOLYGRAF-SRA	Silicone mould release agent	- 60° C to + 250° C	Mold release for rubber, plastics, FRP and non-ferrous metal casting.
MOLYGRAF-PCB-COAT	Conformal Protective coating	- 20° C to + 120° C	Conformal protective coating of Printed Circuit Boards.
MOLYGRAF-RL-30	Solvent based rust remover-cum-cleaner	-	Cleaner-cum-lubricant for splicer, knotter, etc. of winders, knitting, spinning and weaving textile machinery.
MOLYGRAF-A-SPARY	Molybdenum Disulphide and synthetic oil based lubricant spray	- 55° C to + 450° C	Lubrication of bushes, guides, cams, chains, fasteners, bush bearings, sliding surfaces etc in textile weaving, spinning, winding and other machinery.